



PRIME TITANIUM

SPECIAL FEATURES

- ❖ Ultra-High Efficiency, 80 PLUS® Titanium Certified
- ❖ Micro Tolerance Load Regulation
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Premium Hybrid Fan Control
- ❖ Super lower Ripple Noise (under 20 mV) *
- ❖ Extended Hold-up Time (above 30 ms) **
- ❖ Fully Modular Cabling Design
- ❖ Multi-GPU Technologies Supported
- ❖ Gold-Plated High Current Terminals

*under 25 mV for 1000 W

** above 20 ms for 1000 W



POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME 1000 Titanium	25 A 125 W	25 A	83 A 996 W	0.3 A 3.6 W	3 A 15 W	1000 W
PRIME 850 Titanium	20 A 100 W	20 A	70 A 840 W	0.3 A 3.6 W	3 A 15 W	850 W
PRIME 750 Titanium	20 A 100 W	20 A	62 A 744 W	0.3 A 3.6 W	3 A 15 W	750 W
PRIME 650 Titanium	20 A 100 W	20 A	54 A 648 W	0.3 A 3.6 W	3 A 15 W	650 W

WIRE CONFIGURATION

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
PRIME 1000 Titanium	1	2	8	14	5	1
PRIME 850 Titanium	1	2	6	10	5	1
PRIME 750 Titanium	1	2	4	10	5	1
PRIME 650 Titanium	1	2	4	6	5	1



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: L 170 x W 150 x H 86 mm



Specifications may change without prior notice



Headquarters Tel: +886-2-2659-0338 | Fax: +886-2-2659-0530 | sales@seasonic.com | www.seasonic.com
USA Tel: +1 626-969-9966 | Fax: +1 626-969-9986 | ssa.sales@seasonic.com
Europe sse.sales@seasonic.com
Japan Tel: +81-3-6805-4085 | ssj.sales@seasonic.com